

ULTRASONIC WATER BATH



// CABINET:

- 1020 carbon steel;
- Corrosion-resistant;
- Epoxy powder textured coated steel;
- Rubber feet;
- Safety fuse holder;
- Standard drain.

// INTERNAL TANK:

- 304 stainless steel molded;
- No splices and no weldings;
- No angles in bath chamber.

// CONTROL PANEL:

- Panel with 2 digits for timing process;
- Function panel indications;
- Pre set on/off;
- Switch for heating process;
- *Softtouch keys*;
- LED display for time control.



// INCLUDED ACCESSORIES:

- Stainless steel flat cover;
- Stainless steel removable basket;
- Safety fuse.

// OPTIONAL:

- Stainless steel cabinet.



// TECHNICAL DATA:

TIMER	60 minutes – digital timer
HEATING SYSTEM	35°C - Fixed
SET UP CONTROL	Digital pause function
FREQUENCY SET	40Khz
OPERATIONAL CICLE	Automatic
ALARM	Alarm sound in the end of work cycle
POWER CABLE	3 pins – Brazilian Standard (NBR 14136)
HEATING SYSTEM	Shielded resistance
POWER SUPPLY	Up to 15L (110V and 220V) other models - 110V ou 220V (to be defined)

// MODEL DETAILS:

MODEL	CAPACITY	INTERNAL MEASURES	VOLTAGE	POWER
SSBu 3,8L	3.8 liters	10x30x15 cm	110V or 220V	100 W
SSBu 6L	6 liters	10x30x24 cm	110V or 220V	160 W
SSBu 10L	10 liters	15x30x24 cm	110V or 220V	160 W
SSBu 15L	15 liters	20x30x24 cm	110V or 220V	160 W
SSBu 20L	20 liters	15x50x30 cm	110V or 220V	320 W
SSBu 30L	30 liters	20x50x30 cm	110V or 220V	480 W

Notice: Any product presented can be produced according to customer's needs. All models come with English language instruction manual. 1-year warranty against manufacturing defects.